

ZU920T

Ultra bright professional installation laser projector



- 9800 lumen DuraCore laser projector Ultra bright for immersive installations
- Full motorised lens shift Ideal for a simple set-up
- Large zoom range Motorized zoom expands placement opportunities
- Long life Delivers 30,000 hours of virtually maintenance-free operation



At 9,800 lumens with 4K and HDR compatibility, the ZU920T features a dust-resistant IP5X certified optical engine for 24/7 operation

capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include a motorized zoom and focus, full motorized lens shift, and built-in dual 10W speakers.

High brightness, color precision and quiet operation, along with a standard throw lens makes this projector the ideal solution for a variety of end-user scenarios and professional environments, digital signage, edge-blending and projection mapping, simulation, and immersive installations.

Specifications

UPC: 796435 44 589 8, EAN: 5055387666030, Colour: Black Display/image	
Resolution	WUXGA (1920x1200)
Brightness	9,800 lumens
ANSI brightness	8,200
Contrast ratio	3,000,000:1
Contrast ratio - full on/off	1,100:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction -	30°
norizontal	
Keystone correction - vertical	30°
Jniformity	95%
Screen size	1.27m ~ 7.62m (50" ~ 300") diagonal
_amp info	
_ight source type	DuraCore Laser
ASER life	30,000 hours
Optical	
Throw ratio	1.25:1 ~ 2:1
Projection distance (m)	1.33m - 13.06m
loom	1.6
Loom type	Motorised
ocal length (mm)	18.72~29.59
ens shift	Vertical: +/-55%, Horizontal: +/-25%
Native offset	50%
ens shift	Yes - see product downloads for more information
Connectivity	
Connections	Inputs 1 x HDBaseT, 2 x HDMI 2.0, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm
	Outputs 1 × HDMI 2.0, 1 × 3D sync, 1 × USB-A power 1.5A, 1 × Audio 3.5mm
	Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232
AN - wireless networking	No
General	
voise level (min)	29dB
voise level (max)	38dB
Security	Security bar, Kensington Lock
OSD / display languages	9 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
24/7 operation	Yes
60° operation	Yes
Remote control	Backlit ProAV remote
peaker count	2
Vatts per speaker	10W
letworking	
AN - wireless networking	No
AN	Yes
Power	-
ower supply	AC 90 – 264V 50/60 Hz
ower consumption (min)	260W
Power consumption (max)	505W
Weight and dimensions	400 × 400 E × 170
Dimensions (W x D x H) mm	486 x 432.5 x 176
	17.5 kg
Gross weight Net weight	14 kg







Copyright © 2025, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 03042025035846