

3652RK Creative Touch 3-Series 65" interactive flat panel display





- Advanced interaction and collaboration Display Share interactive wireless collaboration toolset
- Advanced touch technology Pen and finger recognition for a seamless experience
- Picture-in-picture (PiP) Run the software solutions you know and love from your laptop while seamlessly annotating in WhiteBoard
- Safe and secure viewing experience Anti-glare and anti-fingerprint, low blue light and flicker free TUV certified

Robust collaboration, extensive connectivity options and a valuefocused design. Combining the latest technology and packed with everything a classroom or business requires, the Creative Touch 3-Series delivers all the functionalities and processing power needed to create, educate and collaborate.



Easily access the front-facing ports for HDMI and USB connectivity. For wireless connectivity, Optoma's Display Share allows up to four users to share content at the same time from their Windows, iOS, macOS, Chrome or Android device.

Specifications

| Display | |
|---|---|
| Back light | Direct type LED |
| Size (diagonal) | 65" |
| Resolution | 3840x2160 |
| Brightness | 400 |
| Contrast ratio | 1,200:1 |
| Contrast ratio (dynamic) | 5,000:1 |
| /iewing angle | 178° |
| Response time | 8ms |
| _ife | 50,000 hours |
| Display colors | 1,070 |
| Speaker count | 2 |
| Watts per speaker Surface hardness | 20W |
| Glass | 7H Anti-Glare + Anti-Fingerprint |
| lase | 4-8% |
| Ambient light sensor | Yes |
| Air gap | 4.00mm |
| Pencil hardness | 9H |
| Physical spec | |
| Dimensions (W x D x H) | 59.53" x 36.3" x 4.53" |
| Wall-hanging screw spec | M8*25mm |
| /ESA holes | 600×400 |
| n the box | European Standard Power Cord 5M |
| | American Standard Power Cord 5M |
| | British Standard Power Cord 1.8M USB touch Cable 3M |
| | USB-C Cable 2M |
| | HDMI Cable 5M |
| | Writing Pen x2 Remote Control |
| | Battery |
| | Pen holder/ Pen tray |
| | QSG |
| Connections | Inputs 3 x HDMI 2.0, 1 x VGA, 1 x DisplayPort, 1 x Audio |
| | 3.5mm, 3 x USB 2.0, 2 x USB 3.0, 1 x RJ45, 1 x USB-C, 1 x |
| | Microphone, 1 x OPS slot Outputs 1 x HDMI 2.0, 1 x S/PDIF, 1 x Audio 3.5mm, 1 x |
| | RJ45 |
| | Control 2 x USB-B interactive, 1 x RS232 |
| Read size (ten) | 22.00mm |
| Bezel size (top) | 54.00mm |
| Bezel size (bottom) Bezel size (left) | 22.00mm |
| Bezel size (right) | 22.00mm |
| Operating conditions | 20% ~ 93% RH |
| Operating temperature (min) | -10°C |
| Operating temperature (max) | 45°C |
| Vet weight | 85.98 lbs |
| Gross weight | 110.23 lbs |
| Wireless - technology | Wifi 6, 2.4G/5G, 2T2R, BT5.2 (AZ832-HN optional) |
| Wireless - operating frequency | 2.4G/5G |
| Fouch system | |
| Sensing type | IR |
| System | Windows10/Windows8/Windows7/Windows XP /Linux - |
| | Debian 10/Mac (1 Touch point only)/Android/Chrome |
| Fouch accuracy | <1.00mm |
| ouch point | 20 android / 40 windows |
| Fouch tool | Finger, Passive infrared pen |
| Pen/finger detection | Yes |
| Power Power supply | 100-240V~ 50/60Hz 3.5A |
| Power supply Power consumption (standby) | 0.5W |
| Power consumption (standby) Power consumption (max) | 0.5VV 300W |
| Power consumption (max) | 145.7 |
| watts) | 170.1 |
| Power consumption - Energy | 136 |
| Star (watts) | |
| Operation System | |
| System version | Android 13 |
| CPU | Quad-core A55 |
| GPU | Dual-core A52 |
| RAM | 4GB |
| | 32GB |
| Storage | |
| Storage OSD / display languages | 20 languages: Arabic, Czech, Danish, Dutch, English, Finnish, |
| - | |







Copyright © 2024 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas InstrumentsTM. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 11122024082625