

# UHD38x

Bright 4K UHD gaming and home entertainment projector



- **4K UHD resolution - HDR and HLG compatible**
- **Lights on viewing - 4000 lumens for use any time of day**
- **Lightning fast gaming projector - Delivers 1080p 240Hz with an ultra-low input lag of 4.2ms**
- **Full 3D compatible - Experience life-like big-screen entertainment**



Immerse yourself in a world of Ultra HD gaming, live sports and TV shows. The UHD38x delivers impressive bright True 4K UHD quality images, lightning-fast input lag as low as 4.2ms and a high refresh rate of 240Hz - perfect for a competitive gaming advantage.

Packed with the latest technology and features, this stylish projector boasts High Dynamic Range (HDR) and HLG compatibility, Full 3D and two HDMI 2.0 ports. Perfect for enjoying life-like big-screen entertainment in any living space.

# Specifications

EAN: 5055387666412, Colour: White

|                                  |   |
|----------------------------------|---|
| <b>Display/image</b>             |   |
| Display technology               | DLP™  |
| Resolution                       | UHD (3840x2160)   |
| Brightness                       | 4,000 lumens  |
| Contrast ratio                   | 1,000,000:1   |
| Native aspect ratio              | 16:9  |
| Aspect ratio - compatible        | 4:3   |
| Keystone correction - horizontal | +/-40°  |
| Keystone correction - vertical   | +/-40°  |
| Horizontal scan rate             | 31 ~ 135Khz   |
| Vertical scan rate               | 24 ~ 120Hz  |
| Uniformity                       | 80%   |
| Screen size                      | 0.84m ~ 7.62m (33" ~ 300") diagonal   |
| <b>Lamp info</b>                 |   |
| Light source type                | Lamp  |
| Lamp watts                       | 240   |
| Lamp life hours (up to)          | 4000 (Bright), 15000 (Dynamic), 10000 (Eco)   |
| <b>Optical</b>                   |   |
| Throw ratio                      | 1.5:1 ~ 1.66:1  |
| Projection distance (m)          | 1.21m - 9.9m  |
| Zoom                             | 1.1   |
| Zoom type                        | Manual  |
| Focal length (mm)                | 15.84 mm~17.42mm/0.624"-0.686"  |
| Lens shift                       | Vertical +0%  |
| Native offset                    | 105%  |
| <b>Connectivity</b>              |   |
| Connections                      | <b>Inputs</b> 2 x HDMI 2.0<br><b>Outputs</b> 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power 1.5A<br><b>Control</b> 1 x RS232, 1 x 12V trigger |
| <b>General</b>                   |   |
| Noise level (min)                | 26dB  |
| Noise level (max)                | 28dB  |
| PC compatibility                 | UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  |
| 2D compatibility                 | 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)   |
| 3D compatibility                 | Frame-pack: 1080p24, 720p50 / 60  |
| 3D                               | Full 3D   |
| Security                         | Security bar, Kensington Lock, Password protected interface   |
| OSD / display languages          | 9 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish                                 |
| Operating conditions             | 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%  |
| Remote control                   | Backlit home remote   |
| Speaker count                    | 1   |
| Watts per speaker                | 10W   |
| In the box                       | AC power cord<br>Remote control<br>2x AAA batteries<br>Basic user manual  |
| Input lag                        | 4.20ms  |
| <b>Power</b>                     |   |
| Power supply                     | 100 ~ 240V, 50 ~ 60Hz   |
| Power consumption (standby)      | 0.5W  |
| Power consumption (min)          | 220W  |
| Power consumption (max)          | 305W  |
| <b>Weight and dimensions</b>     |   |
| Dimensions (W x D x H) mm        | 315 x 270 x 118   |
| Gross weight                     | 4.68 kg   |
| Net weight                       | 3.98 kg   |

