

## ZK400

4K UHD high brightness laser projector









- Laser 4K UHD resolution, HDR and HLG compatible
- DuraCore laser projector 4000 ANSI lumens
- Small form factor with quiet operation
- 30,000 hours maintenance-free laser light source



This feature packed projector is 4K and HDR compatible, has a built-in speaker and its laser technology delivers up to 30,000 hours maintenance-free laser light source.



## **Specifications**

Display/image Display technology DIPTM

Resolution UHD (3840x2160) Brightness 4,000 lumens Contrast ratio 2,000,000:1 16:9 Native aspect ratio Aspect ratio - compatible 4:3 Keystone correction -+/-30° horizontal Keystone correction - vertical +/-30° Has vertical auto keystone Yes

correction

Displayable colours (millions) 1073.4

Horizontal scan rate 15.375 ~ 91.146 Khz Vertical scan rate 50 ~ 120HzHz

Uniformity 75%

0.84m ~ 7.62m (33" ~ 300") diagonal Screen size

Lamp info Light source type LASER life 30,000 hours

Optical 1.5:1 ~ 1.66:1 Throw ratio Projection distance (m) 1.2m - 9.9m Zoom 1.1

Manual Zoom type Focal length (mm) 15.84mm~17.44mm Lens shift Vertical: +/-0% Native offset 105%

Connectivity

Connections Inputs 3 x HDMI 2.0, 1 x USB-A

Outputs 1 x Audio 3.5mm, 1 x S/PDIF Control 1 x RS232, 1 x 12V trigger, 1 x 3D sync

General Noise level (typical) 27dB Noise level (max) 29dB

PC compatibility UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility

NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,

720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D compatibility TBC 3D 3D ready

Security bar, Kensington Lock, Password protected interface Security OSD / display languages

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese

24/7 operation Operating conditions 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 80% Remote control Backlit home remote

Heat dissipation 785BTU/hour Speaker count Watts per speaker 10W AC power cord In the box

> Remote control 2x AAA batteries Basic user manual

Input lag 4.00ms

Optional wireless models UHDCast Pro, QuickCast Bundle, QuickCast starter kit

Power 100V ~ 240V, 50-60Hz Power supply

Power consumption (standby) <0.5W Power consumption (min) 175W Power consumption (max) 230W

Weight and dimensions

337 x 265 x 119.3 mm / 13.27" x 10.43" x 4.7" Dimensions (W x D x H) mm

6.5 kg / 14.33 lbs Gross weight 4.8 kg / 10.58 lbs Net weight UPC 796435 44 627 7





