

HD39HDRx

Big screen gaming and sports anytime of day









- Lights on viewing 4000 lumens
- 4K UHD and HDR compatible
- Lightning fast gaming projector supports 1080p 120Hz with 8.4ms response time
- Easy connectivity 2x HDMI, MHL, USB Power and 10W speaker

Feel the action with the high brightness HD39HDRx. Experience every moment on the big screen for immersive gaming, live sports and movies.

Convenient and easy to set up this compact high brightness projector is ideal for well-lit environments so sports fans can enjoy live action with family or friends with the lights on. Boasting HDR and Amazing colour technology, it delivers accurate true-to-life colour reproduction for movie lovers. It also supports 1080p 120Hz for low input latency of 8.4ms – perfect for games that rely on rapid reactions.

An integrated speaker provides powerful sound and two HDMI inputs enable connection to multiple devices such as set-top boxes, games consoles and HDMI dongles. Weighing less than 2.5kg, you can take it round to a friend's house with the optional carry bag for a sports event, movie night or games marathon anywhere with a flat surface.

Specifications

The following specifications are preliminary and subject to change without notice

Display/image

DIPTM Display technology

Resolution 1080p Full HD (1920x1080) 4,000 lumens

Brightness 50,000:1 Contrast ratio 16:9 Native aspect ratio Aspect ratio - compatible 4.3 Keystone correction - vertical +/-40°

Horizontal scan rate 15.38 ~ 91.15Khz 50 ~ 85(120 for 3D)Hz Vertical scan rate

70% Uniformity

Screen size $0.78m \sim 7.66m$ (30.8" ~ 301.4 ") diagonal

Lamp info Light source type Lamp Lamp watts 240

4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+) Lamp life hours (up to)

Optical

Throw ratio 1.12:1 ~ 1.47:1

Projection distance 1m - 7.5m / 39.37" - 295.28"

Zoom 1.3 Manual Zoom type

Focal length 16.9mm~21.6mm/0.665"~0.85"

Native offset 116%

Connectivity Connections

Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232

General Noise level (typical) 26dB Noise level (max) 28dB

PC compatibility UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA,

VGA, Mac

2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 3D compatibility

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnames

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 85%

Remote control Data remote with laser and mouse function

Speaker count 10W Watts per speaker

AC power cord In the box

2x AAA batteries Basic user manual

Optional wireless models QuickCast Pro 4K

Power

Power supply 100 ~ 240V, 50 ~ 60Hz

Power consumption (standby) 0.5W Power consumption (min) 200W 285W Power consumption (max)

Weight and dimensions

Dimensions (W x D x H) 316 x 244 x 108 mm / 12.44" x 9.61" x 4.25"

Gross weight 3.84 kg / 8.47 lbs 2.91 kg / 6.42 lbs Net weight 796435 81 451 9 UPC

