

## HZ39HDR

Exceptional colors and image quality for home entertainment









- 4,000 ANSI lumens with 300,000:1 contrast ratio
- Flexible installations with 1.3x zoom
- 4K UHD and 1080p HDR (HDMI 2.0) input compatible
- DuraCore maintenance-free laser light source up to 30,000 hours

Bring the cinematic experience home with the incredible 4,000 lumens, 1080p Optoma HZ39HDR laser home theater projector. A DuraCore Laser light source eliminates lamp and filter replacements for up to 30,000 hours of maintenance-free operation with stunning color and image quality throughout the life of the projector.



## **Specifications**

Display/image Display technology DIP Resolution 1080p Full HD (1920x1080) Brightness 4,000 lumens

Yes

Contrast ratio 300,000:1 Native aspect ratio 16:9 Aspect ratio - compatible 4:3 Keystone correction +/-40° vertical

Has vertical auto keystone

correction

Displayable colors 1073.4 (millions)

15.375 ~ 91.146 Khz Horizontal scan rate Vertical scan rate 50 ~ 85 Hz (120Hz for 3D)Hz

Uniformity 85%

28" ~ 300.3" diagonal Screen size

Lamp info Light source type Laser LASER life 30,000 hours Optical 1.21:1 ~ 1.59:1 Throw ratio Projection distance 39.37" - 311.02" Zoom 1.3 Zoom type Manual Focal length (mm) 12.81 mm~16.74mm/0.504"~0.659" Native offset

Connectivity

Connections Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA

(YPbPr/RGB), 2 x Audio 3.5mm

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45, 1 x micro USB service

General Noise level (typical) 30dB Noise level (max) 32dB

UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, PC compatibility

2D compatibility 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(24/50/60Hz), 2160p(24/50/60Hz)

3D compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:

1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D Full 3D

Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

OSD / display languages Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese

(traditional), Turkish, Vietnamese

24/7 operation

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 85%

Remote control Data remote with laser and mouse function Speaker count

10W Watts per speaker In the box AC power cord Remote control

2x AAA batteries Basic user manual 8.40ms

Input lag Optional wireless models WHD200 Networking

LAN - control Yes Power

Power supply 100V ~ 240V, 50-60Hz Power consumption <0.5W

(standby) Power consumption (min) 206W 269W Power consumption (max)

Weight and dimensions

Dimensions (W x D x H) 13.27" x 10.43" x 4.82"

Gross weight 17.2 lbs Net weight 12.13 lbs

