

GT1080HDRx

Go big! Bright short throw home entertainment projector









- Lights on viewing 3800 lumens
- Short throw lens 100" image from just over a yard away
- 4K UHD and HDR compatible
- Lightning-fast gaming projector Supports 1080p 120Hz with 8.4ms response time

Project a 100" image from just over a yard away with the bright GT1080HDRx short throw projector.

Feel the action and experience every moment on the big screen for immersive gaming, live sports and movies.

Convenient and easy to set up this compact high brightness projector is ideal for well-lit environments so sports fans can enjoy live action with family or friends with the lights on. Boasting HDR and Amazing colour technology, it delivers accurate true-to-life colour reproduction for movie lovers. It also supports 1080p 120Hz for low input latency of 8.4ms _ perfect for games that rely on rapid reactions.

An integrated speaker provides powerful sound and two HDMI inputs enable connection to multiple devices such as set-top boxes, games consoles and HDMI dongles. Weighing less than 8lbs. you can take it round to a friend's house with the optional carry bag for a sports event, movie night or games marathon anywhere with a flat surface.

Specifications

The following specifications are preliminary and subject to change without notice Display/image DIPTM Display technology Resolution 1080p Full HD (1920x1080) Brightness 3,800 lumens 50,000:1 Contrast ratio 16:9 Native aspect ratio Aspect ratio - compatible 4:3 16:9 Keystone correction - vertical +/-40° Horizontal scan rate 15.38 ~ 91.15Khz 50 ~ 85(120 for 3D)Hz Vertical scan rate 70% Uniformity 0.92m ~ 7.82m (36.2" ~ 307.8") diagonal Screen size Lamp info Light source type Lamp Lamp watts 240 4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+) Lamp life hours (up to) Optical Throw ratio 0.49:1 Projection distance 0.4m - 3.4m / 15.75" - 133.86" Focal length 7.42mm/0.292" 116% Native offset Connectivity Connections Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support + MHL Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232 General Noise level (typical) 26dB Noise level (max) 28dB UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, PC compatibility VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 2D compatibility 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 3D compatibility 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 3D Full 3D Security Security bar, Kensington Lock, Password protected interface OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max Operating conditions humidity 85% Data remote with laser and mouse function Remote control Speaker count Watts per speaker 10W In the box AC power cord Remote control 2x AAA batteries Basic user manual Lens cap Carry bag QuickCast Pro 4K Optional wireless models Power Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption (standby) 0.5W Power consumption (min) 200W Power consumption (max) 285W Weight and dimensions Dimensions (W x D x H) 12.4"x 4.5" x 9.5" Gross weight 9.5lbs Net weight 7.7lbs UPC 796435 81 452 6