Bright 1080p projection EH334

Superior 1080p performance





CONNECTIVITY (May require optional accessories)





Tablets



3D Blu-ray/DVD Players



1080P



Full 3D



Optoma

Camcorders


Apple TV[®]

Chromecast™

Bright 1080p projection - EH334

OPTICAL/TECHNICAL SPECIFICATIONS

Display Technology	Single 0.48" DMD S410, DC3 chip, DLP® Technology by Texas Instruments
Color Wheel	RYGCWB
Native Resolution	1080p (1920x1080)
Maximum Resolution	WUXGA (1920x1200)
Brightness	3600 ANSI lumens
Contrast Ratio	20,000:1
Displayable Colors	1.07 Billion
Lamp Life and Type*	15,000/12,000/10,000/3500 (Extreme Dimming/Dynamic/ ECO/Bright) - 240W
Projection Method	Front, rear, ceiling mount, table top
Keystone Correction	± 40° vertical
Keystone Distortion	±1% max
Uniformity	70%
Offset	116%±5%
Aspect Ratio	16:9 (native), 4:3, 16:10 and LBX compatible
Throw Ratio	1.47 - 1.62
Projection Distance	3.2' - 35.29" (no zoom)
Image Size	28" - 301
Projection Lens	F=2.41 ~2.53, f=21.85 ~ 24mm manual
Optical Zoom	1.1x
Digital Zoom	0.8 - 2.0
Audio	10W
Noise Level	27/32db
Remote Control	Full size remote
Operating Temperature	41–104°F (5–40°C), 85% max humidity
Power Supply	AC input 100 - 240V, 50 - 60 Hz, auto-switching
Power Consumption	300W typical (Bright mode), 330W max (Bright mode), 210W typical (Eco+ mode), 230W max (Eco+ mode)
High Altitude	Operating temp @ sea level up to 10000 feet = 23F (max); must manually switch to high altitude mode @ 5000 feet & above (using OSD)



COMPATIBILITY SPECIFICATIONS

Computer Compatibility	FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac
Video Input Compatibility	PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p)
3D Compatibility [†]	Side-by-side:1080i50 / 60, 720p50 / 60 Frame-pack: WUXGA24, 720p50 / 60 Over-under: WUXGA24, 720p50 / 60
Vertical Scan Rate	15 - 91kHz
Horizontal Scan Rate	25 - 85Hz (120Hz for 3D)
User Controls	Complete on-screen menu adjustment in 26 languages
I/O Connection Ports	HDMI, VGA-in, composite, audio-in, audio-out, USB power, RS-232C
Loop Through (Audio)	Yes

PHYSICAL SPECIFICATIONS

Security	Security bar, Kensington lock, password protection
Weight	6.75 lbs.
Dimensions (W x H x D)	12.44" x 4.27" x 9.2"

Warranty

1-Year parts and labor limited warranty on the projector, 90 days lamp warranty

What's in the Box

EH334 projector, AC power cord, remote control, carrying case, batteries for remote, multilingual CD-ROM user's manual, quick start card, and warranty card

Source

Resync

User 2Brightness

Optional Accessories

Universal ceiling mount, DLP®Link™ 3D glasses, carry case lamp, remote, HDCast Pro

Accessory Part Numbers

Lamp: BL-FP240G Remote: BR5053C DLP® Link™ 3D glasses: ZD302 Ceiling mount: OCM818W-RU Ceiling mount: BM-5001U Ceiling mount (with extensional pole): OCM815W Single-Cat6 HDBaseT kit: EVBMN-M110 Carrying case: SP.8VH03GC01 Wireless Mirroring: HDCast Pro-Black

Source (

UPC 796435 44 166 1



www.OptomaUSA.com

*Light source life is dependent upon many factors, including brightness mode, display mode, usage, environmental conditions and more. Light source brightness can decrease over time.

^t3D content can be viewed with DLP Link active shutter 3D glasses when projector is used with a compatible 3D player. Please visit www.OptomaUSA.com for more information.

Copyright © 2018 Optoma Technology, Inc. DLP[®] and the DLP logo are registered trademarks of Texas Instruments[™]. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 11192019